

# LinkEx™ Mobile Lighting Unit

Zones: 1, 2, 21 and 22



## Product Overview

Wolf's LinkEx™ Mobile Lighting Unit is a manoeuvrable and flexible lighting solution for quick and easy positioning of four ultra bright LinkEx™ LED Floodlights to immediately deliver a total of 13,200 lumens of panoramic illumination to a task area within a potentially explosive hazardous zone.

The LinkEx™ Mobile Lighting Unit accommodates four high performance, lightweight and portable LinkEx™ LED Floodlights which are ATEX and IECEx certified for safe use in Zone 1 potentially explosive gas, vapour, mist and dust atmospheres, where a T4 temperature class permits. Cable powered and running off voltages of 100 to 254V AC or 24V AC/DC, the unit can accommodate an ATEX Transformer or Splitter Box to manage the power distribution to the individual lights.

Two LinkEx™ LED Floodlights are mounted on height adjustable telescopic poles with a maximum mid light height of 1.7m, and can be raised and lowered and pan a full 360°. Both are held in the desired position with collars and, for extra safety, fail safe locking pins. Two further Floodlights are sited on the upper trolley surface, with a mid light height of 1.1m, with securing pins to prevent any shifting when the trolley is moved. The flexibility of the unit allows these lights to be panned and tilted in situ, or, with their generous cable lengths, individually removed and located at ground level, remote from the trolley, to accommodate task requirements.

The mobile unit, constructed of stainless steel with handles for ease of manoeuvrability, runs on anti-static non-marking lockable castors to fix the unit in position. The lower trolley surface is ideal for housing a transformer or splitter box and storing extra lighting, cabling and tools. Designed to be used on a solid level floor indoors or in an outdoor covered area, it is ideally suited for inspection, painting, maintenance and testing applications requiring high power task lighting which is not only flexible but can be easily moved and positioned.

## Features & Benefits

- Manoeuvrable and flexible task lighting solution
- Quick and easy positioning of four LinkEx™ LED Floodlights
- Delivers a total of 13,200 lumens of panoramic illumination
- ATEX certified for Zone 1 potentially explosive gas, vapour, mist and dust atmospheres
- Runs off voltages of 100 to 254V AC or 24V AC/DC
- Accommodates an ATEX Transformer or Splitter Box
- Two floodlights on height adjustable telescopic poles
- Two floodlights relocatable to ground level
- Constructed of stainless steel with anti-static non-marking lockable castors

## Certifications



1180

# Technical Specification

<b>Product Reference</b>	WF-350
<b>Product Description</b>	LinkEx™ Mobile Lighting Unit
<b>Frame</b>	Stainless Steel
<b>Wheels</b>	x 4 Anti-Static Non-Marking Rubber Wheels (x 2 Lockable)
<b>Dimensions</b>	L 900mm x W 600mm x H 983mm (Trolley Upper Surface to Ground) / Max. 2000mm (From Highest Point to Ground) / Min. 1840mm (When Telescopic Poles Lowered) <u>Mid Light Height</u> Light on Upper Surface – 1100mm Light on Telescopic Pole Max. – 1770mm
<b>Weight</b>	100kg (including lights, power distribution unit and cabling)

- All information has been gathered under laboratory conditions, the user must regard the values given as approximate.
- Changes may be made to the above specification without notification, details are available on request.

Version: SL048 DF364 Issue 1



Wolf Safety Lamp Company, Saxon Road Works, Sheffield, S8 0YA, UK

- T: +44 (0) 114 255 1051 • F: +44 (0) 114 255 7988
- E: [info@wolfsafety.com](mailto:info@wolfsafety.com) • [www.wolfsafety.com](http://www.wolfsafety.com)

